

阻燃系列 Flame-retardant Epoxy Series

品名 Product	混合粘度 Mixed Viscosity	操作期 Pot Life	阻燃类型 Type	填料类型 Fillers	通过认证准 Certificates
GT-712A/B/C-2	800-1200	40-80min	无卤 Halogen-free	需添加 Needed	Docket90、BS-6853
GT-807A/B	350-550	40-70min	低卤 Low-halogen	无需添加 Not needed	UL94V0; DIN5510 (燃烧等级, 烟密度, 熔滴物); RoHS 证书; REACH 证书 UL94V0; DIN5510 classified (Burning Class, Smoke Class, Dripping Class); RoHS; REACH Certificate
GT-807A/B-1	350-550	50-80min			DIN5510 (燃烧等级, 烟密度, 熔滴物); RoHS 证书; REACH 证书 DIN5510 classified(Burning Class, Smoke Class, Dripping Class); RoHS; REACH Certificate
GT-4080A/B	600-1000	>6h	低卤 Low-halogen		UL94V0
GT-908A/B	400-650	40-75min	无卤 Halogen-free	无需添加 Not needed	DIN5510(燃烧等级, 烟密度, 熔滴物) DIN5510 classified(Burning Class, Smoke Class, Dripping Class)
				需添加 Needed	EN 45545-2
GT-910A/B	300-400	80-100min	无卤 Halogen-free	无需添加 Not needed	DIN5510 (燃烧等级, 烟密度, 熔滴物); 烟毒性; RoHS 证书 DIN5510 classified(Burning Class, Smoke Class, Dripping Class); Effluent Toxicity; RoHS Certificate
				需添加 Needed	EN 45545-2